

CATALOG #	AMBIENT TEMPS 12" CHAIN MNT	DLC	BAA COMPLIANT	REPLACES UP TO	WATTS	LUMENS	LPW	ANNUAL SAVINGS	MTG HT. MIN. MAX.	
INDEPENDENCE HIGH BAYS		4500K Standard Also Available in 4000K & 5000K / Suffix 2 indicates Double Module								
	IHB12L	50°C/122°F	5.1 Std	yes	175W MH	79	11,861	150	\$77	12' 16'
	IHB15L	50°C/122°F	5.1 Std	yes	250W MH	105	15,388	146	\$111	12' 18'
	IHB18L	50°C/122°F	5.1 Std	yes	250W MH	123	17,850	146	\$103	14' 20'
	IHB24L	50°C/122°F	5.1 Std	yes	400W MH	164	24,030	147	\$179	18' 30'
	IHBS12-24L	50°C/122°F	5.1 Std	yes	175-400W	83-163	12-24K	158	\$179	12' 30'
	IHB30L	40°C/104°F	5.1 Std	yes	400W MH	185	28,160	152	\$170	20' 35'
	IHB30L2	50°C/122°F	5.1 Std	yes	400W MH	177	28,710	162	\$174	20' 35'
	IHB36L2	50°C/122°F	5.1 Std	yes	1000W MH	245	35,700	146	\$416	25' 40'
	IHB48L2	50°C/122°F	5.1 Std	yes	1000W MH	328	48,060	147	\$379	25' 45'
	IHB60L2	40°C/104°F	5.1 Std	yes	1000W MH	371	56,320	152	\$360	25' 45'
IHB72L3	50°C/122°F	5.1 Std	yes	1000W MH	485	71,697	148	\$311	25' 45'	
IHB90L3	50°C/122°F	5.1 Std	yes	1500W MH	557	88,650	159	\$403	25' 45'	
LINEAR HIGH BAYS										
	ILH29L	60°C/140°F	5.0 Prem	yes	4L T8 FL	72	10,240	143	\$65	10' 14'
	ILH29LL*	60°C/140°F	5.0 Prem	yes	4L T8 FL	72	9,571	134	\$65	10' 14'
	ILHS212L	55°C/131°F	5.1 Std	yes	175W MH	83	12,421	151	\$76	12' 16'
	ILHS212LL*	55°C/131°F	5.1 Std	yes	175W MH	83	11,580	140	\$76	12' 16'
	ILHS215L	55°C/131°F	5.1 Std	yes	250W MH	99	15,277	154	\$114	12' 18'
	ILHS215LL*	55°C/131°F	5.1 Std	yes	250W MH	99	14,353	144	\$114	12' 18'
	ILH218L	50°C/122°F	5.0 Prem	yes	250W MH	145	20,390	141	\$90	14' 20'
	ILH218LL*	50°C/122°F	5.0 Prem	yes	250W MH	145	18,820	130	\$90	14' 20'
	ILH224L	50°C/122°F	5.0 Prem	yes	400W MH	167	25,342	152	\$178	18' 30'
	ILH224LL*	50°C/122°F	5.0 Prem	yes	400W MH	167	23,757	143	\$178	18' 30'
	ILH230L	50°C/122°F	5.0 Prem	yes	400W MH	199	30,716	154	\$164	20' 35'
	ILH230LL*	50°C/122°F	5.0 Prem	yes	400W MH	199	28,757	144	\$164	20' 35'
	ILH415L	50°C/122°F	5.1 Std	yes	250W MH	103	15,720	152	\$125	12' 18'
	ILH415LL*	50°C/122°F	5.1 Std	yes	250W MH	103	14,690	143	\$125	12' 18'
	ILH418L	50°C/122°F	5.1 Std	yes	250W MH	154	21,500	139	\$90	14' 20'
	ILH418LL*	50°C/122°F	5.1 Std	yes	250W MH	154	19,910	129	\$90	14' 20'
	ILHS424L	50°C/122°F	5.1 Std	yes	400W MH	166	25,036	151	\$178	18' 30'
	ILHS424LL*	50°C/122°F	5.1 Std	yes	400W MH	166	23,520	142	\$178	18' 30'
	ILHS430L	50°C/122°F	5.1 Std	yes	400W MH	198	30,352	153	\$164	20' 35'
	ILHS430LL*	50°C/122°F	5.1 Std	yes	400W MH	198	28,519	144	\$164	20' 35'
ILH436L	50°C/122°F	5.1 Std	yes	1000W MH	239	37,515	157	\$418	25' 40'	
ILH436LL*	50°C/122°F	5.1 Std	yes	1000W MH	239	35,364	148	\$418	25' 40'	
ILH448L	50°C/122°F	5.1 Std	yes	1000W MH	334	50,278	151	\$377	25' 45'	
ILH448LL*	50°C/122°F	5.1 Std	yes	1000W MH	334	47,360	142	\$377	25' 45'	
LINEAR DIE CAST HIGH BAYS		Available in 4000K & 5000K Selectable CCT								
	ORHBS12-21L	50°C/122°F	5.1 Prem	no	175-400W	110-150	12-21K	141	\$160	12' 20'
	ORHBS22-30L	50°C/122°F	5.1 Prem	no	400W MH	156-226	22-30K	150	\$127	18' 35'
ROUND HIGH BAYS		5000K Standard Also Available in 4000K								
	IRHS18-30L	50°C/122°F	5.1 Std	no	175-400W	135-252	18-30K	154	\$116	up to 30'
	ORRH18L	50°C/122°F	5.1 Std	no	175W MH	131	18,393	140	\$55	up to 30'
	ORRH24L	50°C/122°F	5.1 Std	no	250W MH	179	23,337	130	\$74	up to 30'
	ORRH30L	50°C/122°F	5.1 Std	no	400W MH	208	30,385	146	\$135	up to 30'
FIELD ADJUSTABLE EDGE-LIT PANELS		Available in 3500K, 4000K & 5000K Selectable CCT								
	FAELP14LED	45°C/113°F	5.1 Std	no	(2) F32-T8	20-40	3,274-4,767	132	\$36	9' 12'
	FAELP22LED	45°C/113°F	5.1 Std	no	(3) F24-T5	25-40	3,385-4,856	133	\$39	9' 12'
	FAELP24LED	45°C/113°F	5.1 Std	no	(4) F32-T8	30-45	3,413-5,046	120	\$56	9' 12'
BACK-LIT PANELS		Available in 3500K, 4000K & 5000K Selectable CCT								
	ORBLP14SEL2-4L	45°C/113°F	5.1 Std	no	(2) F32-T8	15-33	1,875-4,125	125	\$86	9' 12'
	ORBLP22SEL2-4L	45°C/113°F	5.1 Std	no	(3) F24-T5	15-33	1,875-4,125	125	\$100	9' 12'
	ORBLP24SEL3-6L	45°C/113°F	5.1 Std	no	(4) F32-T8	28-48	3,500-6,000	125	\$79	9' 12'
STAIRWELL LIGHTS		4000K Standard Also Available in 3500K & 5000K								
	SWL22L4KUS	-	5.1 Prem	yes	70W MH	16	1,968	123	\$57	8' 10'
	SWL23L4KUS	-	5.1 Prem	yes	70W MH	23	2,967	129	\$54	8' 10'
	SWL45L4KUS	-	5.1 Prem	yes	4L T8 FL	36	5,011	139	\$75	10' 14'
	SWL46L4KUS	-	5.1 Prem	yes	4L T8 FL	44	5,940	135	\$72	10' 14'
	SWL48L4KUS	-	5.1 Prem	yes	4L T8 FL	62	8,044	129	\$64	12' 16'

CATALOG #	AMBIENT TEMPS 12" CHAIN MNT	DLC	BAA COMPLIANT	REPLACES UP TO	WATTS	LUMENS	LPW	ANNUAL SAVINGS	MTG HT MIN MAX
-----------	--------------------------------	-----	------------------	-------------------	-------	--------	-----	-------------------	-------------------

LINEAR WET LOCATIONS

	ILW25LED2D	40°C/104°F	5.1 Std	yes	70W MH	25	3,092	128	\$53	8'	12'
	ILW30LED4D	40°C/104°F	5.1 Std	yes	2L T5 FL	30	4,270	144	\$65	10'	14'
	ILW48LED4D	40°C/104°F	5.1 Std	yes	4L T8 FL	48	7,047	147	\$70	10'	14'
	ILWS4-8L4D	40°C/104°F	5.1 Std	yes	4L T8 FL	27-56	4-8K	147	\$75	8'	14'
	ILW76LED8D	45°C/113°F	5.1 Std	yes	4L T5 FL	76	10,900	147	\$96	12'	16'
	ILW98LED8D	45°C/113°F	5.1 Std	yes	4L T5 FL	98	13,330	142	\$86	14'	18'
	ILWS7-13L8D	45°C/113°F	5.1 Prem	yes	4L T5 FL	45-95	7-13K	154	\$87	12'	18'
	ILW76LED2WD	45°C/113°F	5.1 Prem	yes	4L T5 FL	76	10,620	152	\$96	12'	16'
	ILW98LED2WD	45°C/113°F	5.1 Prem	yes	4L T5 FL	98	13,850	145	\$86	14'	18'
	ILW130LED2WD	45°C/113°F	5.1 Prem	yes	6L T5 FL	130	16,980	132	\$118	14'	20'
	ILW98LED4WD	45°C/113°F	5.1 Prem	yes	4L T5 FL	98	14,040	149	\$86	14'	18'
	ILW130LED4WD	45°C/113°F	5.1 Prem	yes	6L T5 FL	130	17,630	138	\$118	14'	20'
	ILW190LED4WD	45°C/113°F	5.1 Prem	yes	6L T5 FL	190	27,060	145	\$92	16'	22'
	ILWS13-27L4WD	45°C/113°F	5.1 Prem	yes	6L T5 FL	86-184	13-27K	149	\$94	14'	22'
	ILWRK30LED4D	40°C/104°F	5.0 Prem	yes	2L T8 FL	32	4,508	142	\$45	8'	12'
	ILWRK48LED4D	40°C/104°F	5.0 Prem	yes	2L T5 FL	48	6,691	138	\$55	10'	14'
	ILWRK76LED8D	40°C/104°F	5.0 Prem	yes	4L T8 FL	75	10,643	143	\$67	12'	16'
	ILWRK98LED8D	40°C/104°F	5.0 Prem	yes	4L T5 FL	95	13,051	138	\$88	14'	18'
	ILWRK98LED4WD	45°C/113°F	5.0 Prem	yes	4L T8 FL	96	14,120	147	\$58	14'	18'
	ILWRK130LED4WD	45°C/113°F	5.0 Prem	yes	6L T8 FL	130	17,578	135	\$68	14'	20'
	ILWRK190LED4WD	45°C/113°F	5.0 Prem	yes	6L T5 FL	191	27,461	144	\$91	16'	22'

INDEPENDENCE VAPORTITE

	IVT5L45K	40°C/104°F	5.1 Std	yes	4L T8 FL	34	4,849	143	\$85	10'	14'
--	--------------------------	------------	---------	-----	----------	----	-------	-----	------	-----	-----

ORIGIN VAPORTITE

	ORVT44L4K	40°C/104°F	5.1 Prem	no	4L T8 FL	40	4,500	113	\$82	10'	14'
--	---------------------------	------------	----------	----	----------	----	-------	-----	------	-----	-----

STRIPS

	ILS43LL4	40°C/104°F	5.0 Prem	yes	70W MH	23	3,032	134	\$50	8'	10'
	ILS45LL4	40°C/104°F	5.0 Prem	yes	4L T8 FL	38	5,002	130	\$83	10'	14'
	ILS46LL4	40°C/104°F	5.0 Prem	yes	4L T8 FL	44	6,018	137	\$81	10'	14'
	ILS48LL4	40°C/104°F	5.0 Prem	yes	4L T8 FL	61	8,048	132	\$73	12'	16'
	ILS88LL4	40°C/104°F	5.0 Prem	yes	4L T8 FL	61	8,075	133	\$73	12'	16'

ORIGIN STRIPS

	ORST22L	-	5.1 Std	no	70W MH	20	2,564	128	\$50	8'	10'
	ORST44L	-	5.1 Std	no	4L T8 FL	40	4,500	113	\$82	10'	14'
	ORST88L	-	5.1 Std	no	4L T8 FL	65	8,450	130	\$72	12'	16'

TROFFERS

	TLP14S2-4L	50°C/122°F	5.1 Prem	no	(3) F24-T5	20-30	2-4K	137	\$101	9'	12'
	TLP22S2-4L	50°C/122°F	5.1 Std	no	(3) F24-T5	30-40	2-4K	143	\$96	9'	12'
	TLP24S4-6L	50°C/122°F	5.1 Prem	no	(4) F32-T8	32-52	4-6K	148	\$77	9'	12'

CATALOG #	DESCRIPTION	BAA COMPLIANT	FINISH	LETTER COLOR	VOLTS
-----------	-------------	---------------	--------	--------------	-------

EXIT SIGNS

	EXPRWR	Thermoplastic Exit Sign	no	White	Red	120/277
	EXPRWG	Thermoplastic Exit Sign	no	White	Green	120/277
	EXPRWRRC	Thermoplastic Exit Sign - Remote Capable	no	White	Red	120/277
	EXPRWGRC	Thermoplastic Exit Sign - Remote Capable	no	White	Green	120/277
	EECPWR	Thermoplastic LED Exit/Emergency Combo	no	White	Red	120/277
	EECPRWG	Thermoplastic LED Exit/Emergency Combo	no	White	Green	120/277
	EECPWRRC	Thermoplastic LED Exit/Emergency Combo - Remote Capable	no	White	Red	120/277
	EECPWRGRC	Thermoplastic LED Exit/Emergency Combo - Remote Capable	no	White	Green	120/277

EMERGENCY LIGHTS

	EMO2A	Oval 2 Headed Emergency Light	no	White	N/A	120/277
	EMO2ARC	Oval 2 Headed Emergency Light - Remote Capable	no	White	N/A	120/277
	ERD12BZ	Architectural LED Emergency Light	no	Bronze	N/A	120/277
	ERD12WT	Architectural LED Emergency Light	no	White	N/A	120/277

CATALOG #	DESCRIPTION	BAA COMPLIANT	VOLTAGE	TOTAL WATTAGE
-----------	-------------	---------------	---------	---------------

LED REMOTE HEADS

	ERHR12	Single Remote Head - Indoor/Outdoor	no	3.6 Volts	1.17 Watts
	ERHR22	Double Remote Head - Indoor/Outdoor	no	3.6 Volts	2.34 Watts