

HID Ballast Kits

50 – 1000W MH



Metal Halide Ballast Kits

FEATURES

- Attractive Display Carton
- Easy Access Packaging
- No Staples / No Tape
- Starting Temperature -22°F/-30°C

ORDERING INFORMATION

CATALOG #	BALLAST TYPE	BALLAST INPUT VOLT	INPUT WATTS	MAX. INPUT CURRENT	NOM. OPEN CIRCUIT VOLTAGE	FUSE RATING (AMPS)
MH50-0253-KT	HX-HPF	Quad	67	0.64	270	3,2,2,2
MH70-0257-KT	HX-HPF	Quad	91	0.83	260	4,3,2,2
MH100-0204-KT	HX-HPF	Quad	125	1.10	280	7,4,4,3
MH175-0127-KT	CWA-HPF	Quad	205	1.90	296	5,3,3,2
MH175-0005-KT	CWA-HPF	5-Tap	205	1.90	309	5,3,3,2,2
MH250-0145-KT	CWA-HPF	Quad	292	2.50	300	5,5,5,3
MH250-0005-KT	CWA-HPF	5-Tap	292	2.50	300	8,5,5,3,2
MH400-0074-KT	CWA-HPF	Quad	450	4.20	300	10,8,5,5
MH400-0005-KT	CWA-HPF	5-Tap	450	4.20	300	10,8,5,5
MH1000-0005-KT	CWA-HPF	5-Tap	1070	9.00	415	20,15,10,10,10

Quad V - 120/208/240/277 5-Tap - 120/208/240/277/480



Metal Halide Ballast Kits w/ Lamp

FEATURES

- Attractive Display Carton
- Easy Access Packaging
- No Staples / No Tape

ORDERING INFORMATION

CATALOG #	BALLAST TYPE	BALLAST INPUT VOLT	INPUT WATTS	MAX. INPUT CURRENT	NOM. OPEN CIRCUIT VOLTAGE	FUSE RATING (AMPS)	LAMP INCLUDED
MH50-0253MED	HX-HPF	Quad	67	0.64	270	3,2,2,2	MH50/U/M
MH70-0257MED	HX-HPF	Quad	91	0.83	260	4,3,2,2	MH70/U/M
MH100-0204MED	HX-HPF	Quad	125	1.10	280	7,4,4,3	MH100/U/M/P
MH175-0127MED	CWA-HPF	Quad	205	1.90	296	5,3,3,2	MH175/U/M
MH175-0127MOG	CWA-HPF	Quad	205	1.90	296	5,3,3,2	MH175/U
MH175-0005MED	CWA-HPF	5-Tap	205	1.90	309	5,3,3,2,2	MH175/U/M
MH175-0005MOG	CWA-HPF	5-Tap	205	1.90	309	5,3,3,2,2	MH175/U
MH250-0145MOG	CWA-HPF	Quad	292	2.50	300	5,5,5,3	MH250/U
MH250-0005MOG	CWA-HPF	5-Tap	292	2.50	300	8,5,5,3,2	MH250/U
MH400-0074MOG	CWA-HPF	Quad	450	4.20	300	10,8,5,5	MH400/U
MH400-0005MOG	CWA-HPF	5-Tap	450	4.20	300	10,8,5,5	MH400/U
MH1000-0005MOG	CWA-HPF	5-Tap	1070	9.00	415	20,15,10,10,10	MH1000/U

Quad V - 120/208/240/277 5-Tap - 120/208/240/277/480

Kits with Protected Lamps also Available

