

# Linear LED

## Options & Accessories



### INTEGRATED CONTROLS

- Omni-Directional Infrared Motion Sensor
- Photocell Sensor for Daylight Harvesting
- Bi-Level Switching



### MOTION SENSORS


- 2 Interchangeable Application Specific Lenses (Aisle, High Bay, Low Bay)

#### High Bay Lens

TYPICAL MOUNTING HEIGHT:

15-30'

APPLICATION:  
high bay,  
open area




#### Low Bay Lens

TYPICAL MOUNTING HEIGHT:

8-20'

APPLICATION:  
low bay,  
open area




#### High Bay Lens

TYPICAL MOUNTING HEIGHT:

20-40'

APPLICATION:  
high bay,  
open area




#### Low Bay Lens

TYPICAL MOUNTING HEIGHT:

8-20'

APPLICATION:  
low bay,  
open area




#### Aisle Lens

TYPICAL MOUNTING HEIGHT:

20-40'

APPLICATION:  
high bay  
aisle ways



## Options

SUFFIX #	DESCRIPTION
IC	Integrated Control (120-277V)
M	360° Motion Sensor (120 or 277V)
M2	360° Motion Sensor (208, 240, 480V)
M	360° Wet Location Motion Sensor (120, 277V)
M2	360° Motion Sensor (208, 240 or 480V)

## Accessories

CATALOG #	DESCRIPTION
MS360	360° Motion Sensor (120 or 277V)
MS360-480	360° Motion Sensor (208, 240, 480V)
MS360WL	Wet Location Motion Sensor (120, 277V)



### WET LOCATION MOTION SENSORS

- Wet Location 360° Motion Sensor



### CORD SETS

- Available in Several Lengths
- With or Without Molded Plug

## Options

SUFFIX #	DESCRIPTION
3C	3' Cord
3T	3' Cord 120V Plug
3E	3' Cord 208V Plug
3F	3' Cord 240V Plug
3S	3' Cord 277V Plug
10C	10' Cord
10T	10' Cord 120V Plug
10E	10' Cord 208V Plug
10F	10' Cord 240V Plug
10S	10' Cord 277V Plug
20C	20' Cord



# Linear LED Options & Accessories




## HIGH TRANSMISSION LENS

- Frosted Acrylic Lens - 91% Efficiency
- Provides Improved Visual Comfort
- High Impact with Scratch Resistant Surface
- Provides Wider, Smoother & Uniform Light Output
- Protects LEDs

### Options

SUFFIX #	DESCRIPTION
L	Tool-less Snap On Lens



## 45° MOUNTING BRACKET

- For Narrow Wet Location Fixtures
- Mounts the Fixture at a 45° Angle Away from the Wall

### Accessories

CATALOG #	DESCRIPTION
150-103WL45-4	45° Mounting Bracket (Pack of 2)
150-103WL45-8	45° Mounting Bracket (Pack of 3)

### Options

SUFFIX #	DESCRIPTION
W	Wireguard for 75, 104 & 150 Watt - Installed
W	Wireguard for 210 & 310 Watt - installed

### Accessories

CATALOG #	DESCRIPTION
WG33	Wireguard for 75, 104 & 150 Watt
WGH36	Wireguard for 210 & 310 Watt



## WIREGUARD

- Protects Fixture from Hazards
- Tool-less Entry
- Hinges Down



## HANGERS

- Either Chain or Cable Available
- Comes with V-Hooks

### Accessories

CATALOG #	DESCRIPTION
CH36	36" Chain Set (Set of 2)
CH36HFC	36" Chain Set w/Hammer-On Flange
CA36	36" Cable Set (Set of 2)

### Options

SUFFIX #	DESCRIPTION
P	Pendant Mount

### Accessories

CATALOG #	DESCRIPTION
PMK	Pendant Mount Kit



## PENDANT MOUNT

- Accepts 3/4" Rigid Conduit
- Single Point Mounting

### Options

SUFFIX #	DESCRIPTION
H	Hook
F	Inline Fusing (Single)
SP	Surge Protector

### Accessories

CATALOG #	DESCRIPTION
80-SP	Surge Protection
80-HS	Hook Set (2)

