

76-130 Watt

Cold Weather Friendly



2' LED Wet Location

REPLACES UP TO 4L T5 FL / 6L T8 FL / 6L T5 FL



14.5"Wx5.8"Hx26.6"L
13.2 LBS

ILW76LED2WD / ILW98LED2WD / ILW130LED2WD

10,380 / 13,570 / 16,930 **LUMENS** ☀️

76 / 98 / 130 **WATTS** ⚡️

149 / 143 / 132 **LPW** 💰

80 / 80 / 80 **CRI** ⊕

4500K **CCT** 🌞

0-10V **DIMMING** ⬆️⬇️⬇️⬆️

REC MNT HT 📏
12-16 FT / 14-18 FT / 14-20 FT



ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	REPLACES UP TO	VOLTS
ILW76LED2WD	76W LED Wet Location with Glare Free Lens	10,380	4L T5 FL / 6L T8 FL	120-277
ILW98LED2WD	98W LED Wet Location with Glare Free Lens	13,570	4L T5 FL / 6L T8 FL	120-277
ILW130LED2WD	130W LED Wet Location with Glare Free Lens	16,930	6L T5 FL	120-277

Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG #	DESCRIPTION
MS360WL	Wet Location 360° Motion Sensor
80-271CMB	Ceiling Mount Bracket



V Hooks Included

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
xC*	3' Cord (No Plug)	4	480V Driver
EB	Emergency Back-Up		

*x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

ENERGY SAVINGS

LED		HID			
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
76	\$33	4L T5 FL	238	\$129	\$96
76	\$33	6L T8 FL	186	\$107	\$74
98	\$43	4L T5 FL	238	\$129	\$86
98	\$43	6L T8 FL	186	\$107	\$64
130	\$57	6L T5 FL	342	\$175	\$118

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILW76LED2WD	45°C (113°F)
ILW98LED2WD	45°C (113°F)
ILW130LED2WD	45°C (113°F)



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

