

9,000 Lumen

2' Narrow LED High Bay

REPLACES UP TO 100W MH / 4L T8 FL



- ILH29LL / ILH29L
- 9,631 / 10,300 **LUMENS**
- 74 **WATTS**
- 130 / 139 **LPW**
- 80 **CRI**
- 4500K **CCT**
- 0-10V **DIMMING**
- REC MNT HT**
10 FT to 14 FT



4.5"Wx3.3"Hx25.51"L
6.6 LBS

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS
ILH29LL	9,000 Lumen LED High Bay with Glare Free Lens	9,631	120-277
ILH29L	9,000 Lumen LED High Bay - No Lens	10,300	120-277

Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG #	DESCRIPTION
CH36	Chain Set
CH36HFC	Chain Set w/Hammer-On Flange Clip
CA36	Cable Set
MS360	360° Motion Sensor (120, 277V)
MS360-480	360° Motion Sensor (208, 240, 480V)



Hanging Hooks Included

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
xC*	3' Cord (No Plug)	M	Motion Sensor (120, 277V)**
xT*	3' 120V Cord & Plug	M2	Motion Sensor (208, 240, 480V)**
xE*	3' 208V Cord & Plug	P	Pendant Mount
xF*	3' 240V Cord & Plug	IC	Integrated Control**
xS*	3' 277V Cord & Plug	4	480V Driver
EB	Emergency Back-Up		

*x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

**End Panel Mounted

ENERGY SAVINGS

LED			HID		
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
72	\$32	100 MH	129	\$82	\$50
72	\$32	4L T8 FL	151	\$91	\$59

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILH29LL	60°C (140°F)
ILH29L	60°C (140°F)



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

