

18,000 Lumen



4' Narrow LED High Bay REPLACES UP TO 250W MH / 4L T5 FL / 6L T8 FL



7.17"Wx3.30"Hx46.06"L
10 LBS

- ILH418LL / ILH418L
- 19,990 / 21,410 **LUMENS**
- 157 **WATTS**
- 128 / 136 **LPW**
- 80 **CRI**
- 4500K **CCT**
- 0-10V **DIMMING**
- REC MNT HT**
- 14 FT to 20 FT

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS
ILH418LL	18,000 Lumen LED High Bay with Glare Free Lens	19,990	120-277
ILH418L	18,000 Lumen LED High Bay - No Lens	21,410	120-277

Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG #	DESCRIPTION
CH36	Chain Set
CH36HFC	Chain Set w/Hammer-On Flange Clip
CA36	Cable Set
MS360	360° Motion Sensor (120, 277V)
MS360-480	360° Motion Sensor (208, 240, 480V)
WGH33	Wireguard



Hanging Hooks Included

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
xC*	3' Cord (No Plug)	M	Motion Sensor (120, 277V)**
xT*	3' 120V Cord & Plug	M2	Motion Sensor (208, 240, 480V)**
xE*	3' 208V Cord & Plug	P	Pendant Mount
xF*	3' 240V Cord & Plug	W	Wireguard
xS*	3' 277V Cord & Plug	IC	Integrated Control**
EB	Emergency Back-Up	4	480V Driver

*x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

**End Panel Mounted

ENERGY SAVINGS

LED			HID		
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
157	\$69	250 MH	290	\$157	\$88
157	\$69	4L T5 FL	238	\$129	\$60
157	\$69	6L T8 FL	186	\$106	\$37

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILH418LL	50°C (122°F)
ILH418L	50°C (122°F)



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components
*Qualifies for Buy American under ARRA

