

24,000 Lumen

2' LED High Bay

REPLACES UP TO 400W MH / 6L T5 FL



ILH224LL / ILH224L

24,230 / 25,870 **LUMENS**

187 **WATTS**

130 / 138 **LPW**

80 **CRI**

4500K **CCT**

0-10V **DIMMING**

REC MNT HT
18 FT to 30 FT



19.25"Wx3.30"Hx25.50"L
11.2 LBS

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS
ILH224LL	24,000 Lumen LED High Bay with Glare Free Lens	24,230	120-277
ILH224L	24,000 Lumen LED High Bay - No Lens	25,870	120-277

Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG #	DESCRIPTION
CH36	Chain Set
CH36HFC	Chain Set w/Hammer-On Flange Clip
CA36	Cable Set
MS360	360° Motion Sensor (120, 277V)
MS360-480	360° Motion Sensor (208, 240, 480V)

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
xC*	3' Cord (No Plug)	M	Motion Sensor (120, 277V)**
xT*	3' 120V Cord & Plug	M2	Motion Sensor (208, 240, 480V)**
xE*	3' 208V Cord & Plug	P	Pendant Mount
xF*	3' 240V Cord & Plug	IC	Integrated Control**
xS*	3' 277V Cord & Plug	4	480V Driver

EB Emergency Back-Up

*x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

**End Panel Mounted



Hanging Hooks Included

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILH224LL	50°C (122°F)
ILH224L	50°C (122°F)

ENERGY SAVINGS

LED			HID		
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
184	\$81	400 MH	458	\$251	\$170
184	\$81	6L T5 FL	342	\$175	\$94



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

