

# 36,000 Lumen



MANUFACTURED\*  
 & TESTED IN USA

4' LED High Bay  
 REPLACES UP TO 1000W MH



19.25"Wx3.30"Hx46.01"L  
 17.4 LBS

ILH436LL / ILH436L  
 35,120 / 37,540 **LUMENS**   
 249 **WATTS**   
 141 / 151 **LPW**   
 80 **CRI**   
 4500K **CCT**   
 0-10V **DIMMING**   
**REC MNT HT**  
 25 FT to 40 FT

## ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS
ILH436LL	36,000 Lumen LED High Bay with Glare Free Lens	35,120	120-277
ILH436L	36,000 Lumen LED High Bay - No Lens	37,540	120-277

*Specs shown are for 4500K CCT. Also available in 4000K and 5000K. See Cut Sheet for more information.*

## ACCESSORIES

CATALOG #	DESCRIPTION
CH36	Chain Set
CH36HFC	Chain Set w/Hammer-On Flange Clip
CA36	Cable Set
MS360	360° Motion Sensor (120, 277V)
MS360-480	360° Motion Sensor (208, 240, 480V)
WGH36	Wireguard



Hanging Hooks Included

## OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
xC*	3' Cord (No Plug)	M	Motion Sensor (120, 277V)**
xT*	3' 120V Cord & Plug	M2	Motion Sensor (208, 240, 480V)**
xE*	3' 208V Cord & Plug	P	Pendant Mount
xF*	3' 240V Cord & Plug	W	Wireguard
xS*	3' 277V Cord & Plug	IC	Integrated Control**
EB	Emergency Back-Up	4	480V Driver

\*x = 3 for 3' Cord; 6 for 6' cord, 10 for 10' cord; and 20 for 20' cord lengths

\*\*End Panel Mounted

## ENERGY SAVINGS

LED			HID		
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
246	\$108	1000 MH	1080	\$523	\$415

## AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
ILH436LL	50°C (122°F)
ILH436L	50°C (122°F)

200,000+ HOURS



\*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components

