

18,000-30,000 Lumen

LED Round High Bay

REPLACES UP TO 400W MH



IRH18L / IRH24L / IRH30L
19,606 / 24,068 / 29,984

LUMENS
150 / 180 / 235 **WATTS**

LPW
132 / 135 / 129

85 CRI

5000K CCT

0-10V DIMMING

REC MNT HT
Up to 30 FT



13.4"W x 8.26"H
10.81 LBS

- 50°C Ambient Temp rating
- Optional Pendant mount adapter for easy one for one replacement
- Optional optics

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LUMENS	VOLTS
IRH18L	18,000 Lumen LED Round High Bay, 5000K CCT	19,606	120-277
IRH24L	24,000 Lumen LED Round High Bay, 5000K CCT	24,068	120-277
IRH30L	30,000 Lumen LED Round High Bay, 5000K CCT	29,984	120-277

Specs shown are for 5000K CCT. Also available in 4000K. See Cut Sheet for more information.

ACCESSORIES

CATALOG #	DESCRIPTION
RHB16SAR	Spun Aluminum Reflector
RHB16FGC	16" Flat Glass and Clamp Band
RHB16WG	16" Wireguard
RHB16PAR	Prismatic Acrylic Refractor
RHB16CLC	16" Conical Lens and Clamp Band
IRH-PMK	Pendant Mount Adapter Kit; Fits 3/4" NPT

OPTIONS

ADD SUFFIX #	DESCRIPTION	ADD SUFFIX #	DESCRIPTION
M	Motion Sensor	IC	Integrated Control
4	480V Driver		

ENERGY SAVINGS

LED			HID		
WATTAGE	ANNUAL COST	SOURCE WATTAGE	TOTAL WATTAGE USED	ANNUAL COST	ANNUAL SAVINGS
150	\$66	175 MH	210	\$117	\$51
180	\$79	250 MH	290	\$157	\$78
235	\$103	400 MH	458	\$251	\$148

AMBIENT TEMPERATURE FIXTURE RATING

PART #	12" CHAIN MOUNT
IRH18L	50°C (122°F)
IRH24L	50°C (122°F)
IRH30L	50°C (122°F)



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components
*Qualifies for Buy American under ARRA

