



Wall Light Full Selectable

PROJECT INFORMATION

JOB NAME	
FIXTURE TYPE	Selectable Wall Light
CATALOG NUMBER	
APPROVED BY	

SPECIFICATIONS

Construction:

Die cast aluminum housing
UV stabilized powder coated finish

Lens:

Polycarbonate lens

Selectable Lumens and CCT:

Quick and easy to select and set up.

Selectable lumens: 2,280(15W), 4,256(28W), 6,232(41W), 6,840(45W) & 4,588(31W), 8,880(60W), 13,320(90W), 14,800(100W)

Selectable CCTs: 3000K, 4000K and 5000K.

Electrical:

AC Input: 120-277VAC 50/60Hz

Driver: Constant current, Class 2

Includes Photocontrol

LEDs:

Long-life LEDs provide 50,000 hours of operation with at least 70% of initial output (L70).

Listings:

Luminaire is certified to UL/cUL Standards for Wet Locations. DesignLights Consortium qualified luminaire, eligible for rebates from DLC member utilities.

Testing:

Atlas LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 & LM-80.



Warranty:

Five-year limited warranty



DIMENSIONS

Weight: 6.3 lbs.



¹Lumen maintenance values at 25°C are calculated per TM-21 based on LM-80 data and in-situ luminaire testing

Rebates and Incentives are available in many areas. Contact an Atlas Representative for more information.



Wall Light
Full Selectable

ORDERING INFORMATION

ORWP	SEL	2-6L		PC		
PRODUCT SERIES	SELECTABLE	LUMEN PACKAGE	COLOR TEMP.	CONTROLS	VOLTAGE	FIXTURE COLOR
ORWP = Wall Light	SEL = Selectable	2-6L = 2,000 - 6,000 Lumens Selectable 5-14L = 5,000 - 14,000 Lumens Selectable	blank = Selectable 3000K, 4000K, 5000K	PC = 120-277V Photocontrol	Blank = 120-277V	Blank = Bronze

PERFORMANCE DATA

SELECTABLE										
UNIT	CRI	Selectable 3000K CCT		Selectable 4000K CCT		Selectable 5000K CCT		WATTS	BUG RATING	REPLACES UP TO
		DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)			
2 -6L	80	2,280	152	2,280	152	2,280	152	15	B1-U4-G3	175-400W MH
		4,256	152	4,256	152	4,256	152	28		
		6,232	152	6,232	152	6,232	152	41		
		6,840	152	6,840	152	6,840	152	45		
5-14L	80	4,588	148	4,588	148	4,588	148	31	B2-U5-G5	400W MH
		8,880	148	8,880	148	8,880	148	60		
		13,320	148	13,320	148	13,320	148	90		
		14,800	148	14,800	148	14,800	148	100		

DLC PRODUCT INFORMATION

UNIT	DLC PRODUCT ID	CLASSIFICATION
ORWPSEL2-6LPC	PLSF5TXE6YYK	Premium
ORWPSEL5-14LPC	PL028C1GXBN9	Premium