



Independence Series

Tall Wall Light with
Emergency Backup

PROJECT INFORMATION

JOB NAME	
FIXTURE TYPE	Independence Tall Wall Light
CATALOG NUMBER	
APPROVED BY	

SPECIFICATIONS

Construction:

Traditional polycarbonate housing provides proven environmental protection for LED modules. Traditional fixture designs provide a familiar look and standard installation requirements. Retaining this look allows the ability to upgrade fixtures gradually, while retaining the same overall fixture appearance throughout a facility.

Glare Reduction Lens:

Positioning of the LED modules combined with the unique design of the lens assembly results in light being directed to desired locations and reduces offensive light.

Lens assembly is designed to provide high efficiency and to target the light where needed to satisfy outdoor lighting requirements.

Thermal Management:

Atlas' Patent Pending exclusive Thermal Management System™ features a unique internal design that allows for lower operating temperatures which results in a brighter, whiter light, more stable color and longer LED (200,000+ hrs¹) and driver life.

Listings:

Luminaire is certified to UL/cUL Standards for Wet Locations DesignLights Consortium qualified luminaire, eligible for rebates from DLC member utilities. ²See chart on other next page for

AC Input: 120/208/240/277V

Driver:

Constant current, Class 2, 120-277 VAC, 50-60 Hz
High Efficiency – min. 84%
Off-State Power: 0 Watts
Dimming: 0-10V

LEDs:

Available in 4000K, 4500K and 5000K CCT
Atlas LEDs provide higher lumen output, greater energy efficiency and more reliable fixture performance.

Reduced Glare:

Positioning of the LED modules within the housing result in light directed to desired locations and reduces offensive light.

Testing:

Atlas LED luminaires have been tested by an independent laboratory in accordance with IESNA LM-79 & LM-80.

Warranty: Five-year limited warranty

Installation:

Fixture retains the same knock-out sizes and positions as previous models, reducing wiring costs.

Emergency Battery Back Up: For factory installed Emergency Back-Up add suffix EB to part number. Provides emergency illumination (1,580 lumens) for a minimum of 90 minutes. (Requires larger back housing.)





BUY AMERICAN



COMPLIANT*



DIMENSIONS

Weight: 6.6 lbs.



Weight: 10.7 lbs.

Emergency Battery Back Up requires larger back housing



¹LED Life Span Based Upon LM-70 Test Results



Independence Series Tall Wall Light



ORDERING INFORMATION

W	S	2L					
PRODUCT SERIES	SELECTABLE	LUMEN PACKAGE	COLOR TEMP.	CONTROLS	VOLTAGE	FIXTURE COLOR	OPTIONS
W = Wall Light	blank = Fixed	2L = 2,000 Lumens	4K = 4000K 45K = 4500K 5K = 5000K	PC = 120V Photocontrol Installed PM = 120-277V Photocontrol Installed	Blank = 120-277	Blank = Bronze	EB = Emergency Back-up SP = Surge Protection
	S = Selectable	2L = 2,000 Lumens	blank = Selectable (4000K, 4500K, 5000K)	blank = 120-277V Photocontrol Installed LP = Less Photocontrol			

PERFORMANCE DATA

FIXED

LUMEN PACKAGE	CRI	4000K CCT		4500K CCT		5000K CCT		WATTS	BUG RATING	REPLACES UP TO
		DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)			
2L	80	2,283	112	2,133	110	2,285	112	21	B1-U3-G2	100W MH

SELECTABLE CCT

LUMEN PACKAGE	CRI	Selectable 4000K CCT		Selectable 4500K CCT		Selectable 5000K CCT		WATTS	BUG RATING	REPLACES UP TO
		DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)	DELIVERED LUMENS	EFFICACY (LPW)			
2L	80	2,254	124	2,305	130	2,316	127	18	B1-U3-G2	100W MH

DLC PRODUCT INFORMATION

FIXED

LUMEN PACKAGE	4000K CCT		4500K CCT		5000K CCT	
	DLC PRODUCT ID	CLASSIFICATION	DLC PRODUCT ID	CLASSIFICATION	DLC PRODUCT ID	CLASSIFICATION
2L	n/a	n/a	n/a	n/a	n/a	n/a

SELECTABLE CCT

UNIT	DLC PRODUCT ID	CLASSIFICATION
WS2L	S-X41GAK	Standard